

[Home](#) > [Georg Fischer](#) > [Signet](#) > [Instrumentation](#) > [Flow](#) > [Instruments](#) > 3-5090

Signet 3-5090 Flow Instrument

Item#: 198825000 | Model#: 3-5090 Series#: 3-5090

**Description:**

3-5090 Sensor-Powered ProPoint Flow Monitor

Price: USD \$0⁰⁰[Buy Now](#)

Technical Specification

Series Data

Operating Range	0.3 to 6 m/s (1 to 20 ft/s) in pipes DN15 to DN900 (½ to 36 in.) 7 ft/s (min. full scale range)
Display	Taut-band suspension meter movement, 250° deflection (not suitable for prolonged exposure to vibration)
Repeatability	±1% of full scale
Enclosure Materials	ABS Plastic
Panel and Case Gasket	Neoprene
Window	Hard-coated Polycarbonate
Power Requirements	None
Operating Temperature	-10 °C to 65 °C (14 °F to 149 °F)
Relative Humidity	0 to 95%, non-condensing
Environmental Enclosure	NEMA 4X/IP65 (front face only)
Type	Flow Monitor
Series	5090

Product Dimensions

Weight	0.99 lb
Width	300.00 mm, 11.81 in
Height	100.00 mm, 3.94 in
Length	200.00 mm, 7.87 in

Technical Documents

Document Title	Download
Datasheet	Click Here to Download
Instruction Manuals (English)	Click Here to Download
Instruction Manuals (French)	Click Here to Download
Instruction Manuals (German)	Click Here to Download
Instruction Manuals (Spanish)	Click Here to Download

Accessories

ID	Short Details	Price
3-0000.596	Heavy duty wall mount bracket	\$113.00 \$110.44
3-5000.395	Splashproof rear cover, for ProPoint	\$86.00
3-5000.399	Panel adapter, 5in x 5in to 1/4 DIN	\$61.00
3-5000.598	Surface mount bracket	\$58.00
3-9000.392	Liquid tight connector kit, (3) connectors	\$92.00
3-9000.392-1	Liquid tight connector, (1) NPT connector	\$38.00

[3-9000.392-2](#)

Liquid tight connector, (1) PG13.5 connector

\$38.00

