


Communications made easy

PROFIBUS in a nutshell

...is the world's most successful fieldbus with 50.9 million devices installed by the end of 2014 with over 9 million of these in the process industries.



The reliable and simplified communication protocol for your industrial applications.

The Signet 0486 Profibus Concentrator allows for simplified connection of Signet sensors to a PROFIBUS network. The 0486 supports six sensor interfaces and a 4 to 20 mA current loop proportional valve interface. The 0486 supports PROFIBUS DP V1 and is available with either DB9 or M12 network connectors.

Ask us about other communications needs.

- PROFINET
- ETHERNET/IP

Integrates up to six sensors to one PROFIBUS address

PROFIBUS integration adapted to your needs.

Using the PROFIBUS protocol, devices from different manufacturers exchange information on the same communications bus without the need for special interface equipment.



Multiple channels in a single device

By using a single PROFIBUS cable, other wiring is reduced significantly, and overall installation costs are dramatically reduced.


- Six Signet sensor interfaces (S³L)
- Sensor interface supports all Signet (S³L) sensors
- Four shared frequency inputs for flow measurements
 - 515, 525, 2536, 2540 and other frequency flow devices
- Two shared 4 to 20 mA current loop inputs for other instruments
- Sensor interfaces supports Signet 8059
 - Four dry-contact SPDT relays in a single device (maximum of 24 relays)


- Sensor interface supports Signet 8058 iGo devices
 - Single 4 to 20 mA inputs (maximum of six, 4 to 20 mA inputs)
- One dedicated current loop I/O for valve positioning control or other loop uses
 - 4 to 20 mA output
 - 4 to 20 mA input



*Simplicity

- · Easy assembly
- · Proper and faster installation
- · Less cabinet space needed
- Fast troubleshooting and easier maintenance
- Less engineering costs to integrate sensors and automation products into Fieldbus
- Reduces PROFIBUS integration cost per installation
- Full digital access to GF sensor analytics and diagnostics







LED	Description	S3L
O	Off	Not Configured
	Green	Configured and Working
O	Green Flash	Configured and Sensor Error
	Red	Configured and Wrong Device
	Red Flash	Configured and No Device

Programming

Setting-up process control has been dramatically improved using real engineering units and not bits or mA values. By using GF sensors and valves, control logic can be programmed in real process variables.

Improved GSD Instruction

The GSD is loaded into the PLC software programming environment, which allows the programmer to configure the Concentrator with sensors and devices specific for their application. All programming and configuration data is stored in the PLC/Automation software. Reducing configuration and set up errors while simplifying documentation and version management.

Installation and Maintenance

LED lights indicate the configuration of each channel and operation readiness simplifying field troubleshooting.





+Features \rightarrow **Advantages** \rightarrow **Benefits**

Sensor specific GSD features.	GSD sensor setup using engineering units and pull down menus reducing time, and errors in configuring the Profibus Concentrator for your specific applications.	Reduced errors Ease of programming and configuration.
Simple LED indicators for on-site troubleshooting and verification.	Each channel's configuration and status is shown by LEDs to simplify installation and troubleshooting.	Eases troubleshooting and configuration of field units.
Fully programmed over Profibus network.	All configuration is created in your automation software package (PLC/PAC). Simplifies software development, documentation and configuration. Reduces errors.	Configuration is contained in your automation software package. Eliminates documentation of manual configuration and programing of multiple devices.
Control external devices with internal current loop I/O or compatible GF Signet external 4 channel Relay Module.	Control and sensing in a single unit on a single Profibus address. Fail safe operation sets outputs to safe value in case of communication failure.	Sense and control in single device. Protection from communication failures.
Access to measurement and diagnostic data stored in GF Signet sensors.	Access to multiple measurements from a single sensors. Status message ensure correct operation of the sensors.	Reduces the number of physical sensors required in many applications. Increases reliability of automation systems.
 Six Signet (S³L) Channels and One Current Loop I/O Channel. Four (S³L) Channels support frequency input for low cost flow devices. Two (S³L) Channels support current loop inputs. 	Conserves Profibus Addresses by combining connections and configuration in a single device. Mix and Match sensor technology, (S³L), Frequency, and or current loop, to match your application.	Lowers cost of installation of multiple sensors and valves. Interface multiple types of sensors in a single device, (S ³ L), frequency, and or current loop.



Common Process Applications



Tying the different measurement sensors and valves back to the primary control system can be greatly simplified through the use of the GF Profibus Concentrator, reducing costs, maintenance and engineering time. Examples are highlighted below.

Reverse Osmosis

Reverse osmosis is a physical process for purification of water. Some key challenges users may face, are maintaining unit performance to design parameters and maximizing service life. Typical instrumentation include chlorine measurement to protect the membrane, pH, Flow and conductivity to monitor the process.


- Detect Chlorine in influent
- Monitor and control pH
- Monitor flow
- · Monitor influent, product and reject conductivities

Cooling Towers

Cooling towers and heat recovery systems are a key element for the energy balance of all cooling systems. Typical instrumentation for this process operation includes pH, conductivity, and with additional flow and valve control to monitor unit performance.

- Monitor and control system conductivity levels
- · Monitor make up and bleed off volumes
- Monitor and control pH levels
- Monitor and control biocide levels







Cooling Tower (pH, ORP, Conductivity, Make Up Flow, Blow Down Flow)	Number of Transmitters	Number of Readings and Statuses	# of Wires or Cables to Automation System
Single Channel Transmitter	5	12	10
Multi-Channel (4) Transmitter	2	12	10
Profibus Concentrator	1	39	1

Fume/Gas Scrubbing

Exhaust gases must be cleaned before being released into the atmosphere. As the contaminated gas flows into the washer, the harmful substances are washed out on spraying levels so that the clean gas rises and can be emitted. Typical instrumentation include, pH, flow, level and pressure.

- Monitor and control of wet scrubber pH
- Monitor pump flow rates
- Monitor sump liquid levels
- Monitor pump pressure
- Measure blow down



Fume Scrubber (Recirculation: Pump Flow, Pump Pressure. Sump: pH, Liquid Level, Conductivity. Blow Down Flow and Total)	Number of Transmitters	Number of Readings and Statuses	# of Wires or Cables to Automation System
Single Channel Transmitter	6	12	12
Multichannel (4) Transmitter	2	12	12
Profibus Concentrator	1	43	1

Solution of applications

- Automation Upgrades
- Filter and RO Skids
- Neutralization Systems
- Cooling Tower Automation
- Water and Wastewater Treatment
- Boiler Feed Water and Condensate Monitoring

Worldwide at home

Our sales companies and representatives ensure local customer support in over 100 countries.

www.gfsignet.com

Argentina / Southern South America Georg Fischer Central Plastics Sudamérica S.R.L. Buenos Aires, Argentina Phone +54 11 4512 02 90 gfcentral.ps.ar@georgfischer.com www.gfps.com/ar

Australia George Fischer Pty Ltd Riverwood NSW 2210 Australia Phone +61 (0) 2 9502 8000 australia.ps@georgfischer.com www.gfps.com/au

Austria Georg Fischer Rohrleitungssysteme GmbH 3130 Herzogenburg Phone +43 (0) 2782 856 43-0 austria.ps@georgfischer.com www.gfps.com/at

Belgium / Luxembourg Georg Fischer NV/SA 1070 Bruxelles/Brüssel Phone +32 (0) 2 556 40 20 be.ps@georgfischer.com www.gfps.com/be

Brazil Georg Fischer Sist. de Tub. Ltda. 04795-100 São Paulo Phone +55 (0) 11 5525 1311 br.ps@georgfischer.com www.gfps.com/br

Canada Georg Fischer Piping Systems Ltd Mississauga, ON L5T 882 Phone +1 (905) 670 8005 Fax +1 (905) 670 8513 ca.ps@georgfischer.com www.gfps.com/ca

Georg Fischer Piping Systems Ltd Shanghai 201319 Phone +86 21 3899 3899 china.ps@georgfischer.com www.gfps.com/cn

China

Denmark / Iceland Georg Fischer A/S 2630 Taastrup Phone +45 (0) 70 22 19 75 info.dk.ps@georgfischer.com www.gfps.com/dk

Finland Georg Fischer AB 01510 VANTAA Phone +358 (0) 9 586 58 25 Fax +358 (0) 9 586 58 29 info.fi.ps@georgfischer.com www.gfps.com/fi France Georg Fischer SAS 95932 Roissy Charles de Gaulle Cedex Phone +33 (0) 1 41 84 68 84 fr.ps@georgfischer.com www.qfos.com/fr

Germany Georg Fischer GmbH 73095 Albershausen Phone +49 (0) 7161 302-0 info.de.ps@georgfischer.com www.gfps.com/de

India Georg Fischer Piping Systems Ltd 400 076 Mumbai Phone +91 224007 2001 branchoffice@georgfischer.com www.gfps.com/in

Indonesia George Fischer Pte Ltd – Representative Office Phone +62 21 2900 8564 Fax +62 21 2900 8566 sgp.ps@georgfischer.com www.gfps.com/sg

Italy Georg Fischer S.p.A. 20063 Cernusco S/N (MI) Phone +39 02 921 861 it.ps@georgfischer.com www.gfps.com/it

Japan Georg Fischer Ltd 556-0011 Osaka, Phone +81 (0) 6 6635 2691 jp.ps@georgfischer.com www.gfps.com/jp

Korea Georg Fischer Piping Systems 271-3 Seohyeon-dong Bundang-gu Seongnam-si, Gyeonggi-do Seoul 463-824 Phone +82 31 8017 1450 Fax +82 31 8017 1454 kor.ps@georgfischer.com www.gfps.com/kr

Malaysia George Fischer (M) Sdn. Bhd. 40460 Shah Alam, Selangor Darul Ehsan Phone +60 (0) 3 5122 5585 Fax +603 5122 5575 my.ps@georgfischer.com www.gfps.com/my

Mexico / Northern Latin America Georg Fischer S.A. de C.V. Apodaca, Nuevo Leon CP66636 Mexico Phone +52 (81) 1340 8586 Fax +52 (81) 1522 8906 mx.ps@georgfischer.com www.gfps.com/mx Middle East Georg Fischer Piping Systems (Switzerland) Ltd Dubai, United Arab Emirates Phone +971 4 289 49 60 gcc.ps@georgfischer.com www.gfps.com/int

Netherlands Georg Fischer N.V. 8161 PA Epe Phone +31 (0) 578 678 222 nl.ps@georgfischer.com www.gfps.com/nl

New Zealand Georg Fischer Ltd 13 Jupiter Grove, Upper Hutt 5018 PO Box 40399, Upper Hutt 5140 Phone +64 (0) 4 527 9813 nz.ps@georgfischer.com www.gfps.com/nz

Norway Georg Fischer AS 1351 Rud Phone +47 67 18 29 00 no.ps@georgfischer.com www.gfps.com/no

Philippines George Fischer Pte Ltd Representative Office Phone +632 571 2365 Fax +632 571 2368 sgp.ps@georgfischer.com www.qfps.com/sq

Poland Georg Fischer Sp. z o.o. 05-090 Sekocin Nowy Phone +48 (0) 22 31 31 0 50 poland.ps@georgfischer.com www.gfps.com/pl

Romania Georg Fischer Piping Systems (Switzerland) Ltd 020257 Bucharest - Sector 2 Phone +40 (0) 21 230 53 80 ro.ps@georgfischer.com www.gfps.com/int

Russia Georg Fischer Piping Systems (Switzerland) Ltd Moscow 125047 Phone +7 495 258 60 80 ru.ps@georgfischer.com www.gfps.com/ru Singapore
George Fischer Pte Ltd
11 Tampines Street 92, #04-01/07
528 872 Singapore
Phone +65 6747 0611
Fax +65 6747 0577
sgp.ps@georgfischer.com
www.gfps.com/sg
Spain / Portugal
Georg Fischer S.A.
28046 Madrid
Phone +34 (0) 91 781 98 90
es.ps@georgfischer.com
www.gfps.com/es

Sweden Georg Fischer AB 117 43 Stockholm Phone +46 (0) 8 506 775 00 info.se.ps@georgfischer.com www.qfps.com/se

Switzerland Georg Fischer Rohrleitungssysteme (Schweiz) AG 8201 Schaffhausen Phone +41 (0) 52 631 30 26 ch.ps@georgfischer.com www.gfps.com/ch

Taiwan Georg Fischer Co., Ltd San Chung Dist., New Taipei City Phone +886 2 8512 2822 Fax +886 2 8512 2823 www.gfps.com/tw

United Kingdom / Ireland George Fischer Sales Limited Coventry, CV2 2ST Phone +44 (0) 2476 535 535 uk.ps@georgfischer.com www.gfps.com/uk

USA / Caribbean Georg Fischer LLC Irvine, CA 92618-1904 Phone +1 (714) 731 88 00 Toll Free 800 854 40 90 us.ps@georgfischer.com www.gfpiping.com

International Georg Fischer Piping Systems (Switzerland) Ltd 8201 Schaffhausen/Switzerland Phone +41 (0) 52 631 30 03 Fax +41 (0) 52 631 28 93 info.export@georgfischer.com www.gfps.com/int

The technical data is not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability They are subject to modification. Our General Terms of Sale apply.

